

## **Wikiprint Book**

**Title: How to install your environment on redhat8 (skl and rome)**

**Subject: Igcmg\_doc - Doc/ComputingCenters/TGCC/IreneRedHat8**

**Version: 78**

**Date: 07/05/24 14:24:20**

## Table of Content

<b>Porting on RedHat8</b>	<b>3</b>
<b>How to install your environment on redhat8 (skl and rome)</b>	<b>3</b>
<b>Modifications need to be done in models</b>	<b>3</b>
LMDZ	3
ORCHIDEE	3
INCA	3
XIOS	4
<b>Modifications for V6.2 configurations</b>	<b>4</b>
Compilation and computation	4
post-processing	4
<b>Modification for v6.1 configurations and older ones</b>	<b>4</b>
compilation	4
Computation	5

## Porting on RedHat8

After maintenance of April 11 and 12 all the Irene machines of the TGCC will change OS (it will go from redhat7 to redhat8)

### How to install your environment on redhat8 (skl and rome)

We suggest the user to use the igcmg environment (in bash) with a copy of the bashrc in his HOME.

```
ryyy999@irene: cp ~/igcmg/MachineEnvironment/irene_next/bashrc ~/.bashrc
ryyy999@irene: cp ~/igcmg/MachineEnvironment/irene_next/bashrc_irene_next ~/.bashrc_irene_next
```

Additionally, you can complete the example of bashrc\_irene\_next file to create your favorite environment (alias, module load ...).

*We strongly advice you to add the line `module switch dfldatadir dfldatadir/genXXXX` in your own `.bashrc_irene_next`.*

WARNING : if you have a `~/profile` file, it's better to remove it to avoid any problem during the execution of a simulation with libIGCM

In this environment is specified:

the path to the compiler tool `fcm` and to the `rebuild` tool which recombines output files from a parallel model:

```
export PATH=$(ccc_home -u igcmg)/Tools/fcm/bin:$(ccc_home -u igcmg)/Tools/irene/bin:$PATH
```

- the load of modules giving access to analyze data or post processing libraries and tools needed on our platform (done in `ccc_home -u igcmg/MachineEnvironment/irene_next/env_atlas_irene`).



WARNING : You cannot load in the same time the intel environment for compilation and models computation, AND ferret software. There are not compatible. It's why by default we propose an environment for post processing. The computation environment will be loaded by `modipsl` and `libIGCM` during the compilation and the running time.

### Modifications need to be done in models

#### LMDZ

modify `%BASE_LD` in `LMDZ/arch/arch-X64_IRENE.fcm`

```
%BASE_LD -i4 -r8 -auto -L/ccc/products/mkl-20.0.0/system/default/20.0.0/mkl/lib/intel64 -lmkl_intel_lp64 -lmkl_core -lmkl
```

#### ORCHIDEE

If you are working with a version older than rev 7792, you need to apply modifications described [here](#).

#### INCA

If you are working with a version older than rev 1050, you need to modify `lunout` parameter to use standard output file. For this in `INCA/src/INCA_MOD/print_inca.F90` remove lines from

```
namefile='inca.out'

(...)

stop 'print_inca'
endif
```

add line

```
lunout = 6
```

## XIOS

If you are working with a version on XIOS/branches/xios-2.5, you need to modify XIOS/arch/arch-X64\_IRENE.fcm

```
%BASE_CFLAGS      -std=gnu++98 -diag-disable 1125 -diag-disable 279 -D__XIOS_EXCEPTION
```

## Modifications for V6.2 configurations

### Compilation and computation

Modify ARCH/arch-X64\_IRENE.env

```
# Compile and running environnemnet at Irene Skylake

module purge
module load intel/20.0.0
module load mpi/openmpi/4.1.4
module load flavor/hdf5/parallel
module load hdf5/1.12.0
module load netcdf-fortran/4.5.3
module load mkl/20.0.0
module load feature/bridge/heterogenous_mpmc
module load c++/gnu/8.3.0
module load c/gnu/8.3.0
```

### post-processing

Modify libIGCM/libIGCM\_sys/libIGCM\_sys\_irene.ksh or libIGCM\_sys\_irene-amd.ksh to source new env\_atlas\_irene file.

```
if [ X${TaskType} = Xcomputing ] ; then
  IGCM_debug_Print 1 "Modules will be loaded later in IGCM_sys_activ_variables."
else
  module purge > /dev/null 2>&1
  . $( ccc_home -u igcmg)/MachineEnvironment/irene_next/env_atlas_irene > /dev/null 2>&1

  export PCMDI_MP=/ccc/work/cont003/igcmg/igcmg/PCMDI-MP
  export UVCDAT_ANONYMOUS_LOG=FALSE
fi
```

## Modification for v6.1 configurations and older ones

### compilation

- Create a directory config/.../ARCH/ and create in it the file arch-X64\_IRENE.env

```
# Compile and running environnemnet at Irene Skylake

module purge
module load intel/20.0.0
module load mpi/openmpi/4.1.4
module load flavor/hdf5/parallel
module load hdf5/1.12.0
module load netcdf-fortran/4.5.3
module load mkl/20.0.0
module load feature/bridge/heterogenous_mpmc
module load c++/gnu/8.3.0
module load c/gnu/8.3.0
```

- Modify AA\_make to source this new environment file and indicate to XIOS which environment file it will use

```
submitdir=$(shell pwd)
arch_path=${submitdir}/ARCH/

all :
    if [ -s ../resol ] ; then $(M_K) `head -1 ../resol |cut -c 8-` ; else $(M_K) LMD144142-L79 ; fi

(...)

xios :
    (cd ../../modeles/XIOS ; ./make_xios --prod --arch ${FCM_ARCH} --arch_path ${arch_path} --job 4 ; cp bin/

libioipsl : ../../modeles/IOIPSL/src
    (. ${arch_path}/arch-X64_IRENE.env; cd ../../modeles/IOIPSL/src ; $(M_K) -f Makefile)
```

For older configurations you may have to source the arch.env file for all the models other than XIOS (applies for IPSLCM5A2 but could be needed for others).

In that case add `. ${arch_path}/arch-X64_IRENE.env;` before the command that changes the directory in every models rules except for xios where the previous changes are enough.

IPSLCM5A2 Makefile:

```
oasis3-mct:
    (. ${arch_path}/arch-X64_IRENE.env; cd $(OASIS_DIR)/util/make_dir ; cp $(MYSRC_DIR)/SOURCES/OASIS3-MCT/make_${FCM_ARCH}

liborchidee : ../../modeles/ORCHIDEE/
    (. ${arch_path}/arch-X64_IRENE.env; cd ../../modeles/ORCHIDEE/ ; ./makeorchidee_fcm -parallel mpi_omp -arch $(FCM_ARCH)

...

lmdz: ../../modeles/LMDZ
    (. ${arch_path}/arch-X64_IRENE.env; cd ../../modeles/LMDZ; ./makelmdz_fcm -d $(RESOL_LMDZ) -arch $(FCM_ARCH) -j 8 ce01
    (. ${arch_path}/arch-X64_IRENE.env; cd ../../modeles/LMDZ ; ./makelmdz_fcm -d $(RESOL_LMDZ) -mem -cosp false -v true -p

paleolmdz: ../../modeles/LMDZ
    (. ${arch_path}/arch-X64_IRENE.env; cd ../../modeles/LMDZ; ./makelmdz_fcm -d $(RESOL_LMDZ) -arch $(FCM_ARCH) -j 8 ce01
    (. ${arch_path}/arch-X64_IRENE.env; cd ../../modeles/LMDZ ; ./makelmdz_fcm -d $(RESOL_LMDZ) -mem -cosp false -v true -p

...

orca2lim2: ../../modeles/NEMOGCM/CONFIG
    (. ${arch_path}/arch-X64_IRENE.env; cd ../../modeles/NEMOGCM/CONFIG; cp ../../../../config/IPSLCM5A2/SOURCES/NEMO/arch-${FCM_ARCH}

paleorca2lim2: ../../modeles/NEMOGCM/CONFIG
    (. ${arch_path}/arch-X64_IRENE.env; cd ../../modeles/NEMOGCM/CONFIG; cp ../../../../config/IPSLCM5A2/SOURCES/NEMO/arch-${FCM_ARCH}
```

- create the Makefile as explain [here](#)
- clean everything on previous compilations :

```
gmake clean
```

- compile

## Computation

- Extract a new version of libIGCM

```
svn co -r 1579 https://forge.ipsl.jussieu.fr/libigcm/svn/trunk/libIGCM libIGCM
```

- Modify config.card file to add environment file parameter :

```
EnvFile=${SUBMIT_DIR}/../ARCH/arch.env
```