

## **Wikiprint Book**

**Title: Trac Backup**

**Subject: Igcmg\_doc - TracBackup**

**Version: 1**

**Date: 06/29/24 09:43:31**

## Table of Content

<b>Trac Backup</b>	<b>3</b>
Creating a Backup	3
Restoring a Backup	3

## Trac Backup

Since Trac uses a database backend, some extra care is required to safely create a backup of a [project environment](#). Luckily, [trac-admin](#) has a command to make backups easier: `hotcopy`.

*Note: Trac uses the `hotcopy` nomenclature to match that of [Subversion](#), to make it easier to remember when managing both Trac and Subversion servers.*

### Creating a Backup

To create a backup of a live [TracEnvironment](#), simply run:

```
$ trac-admin /path/to/projenv hotcopy /path/to/backupdir
```

[trac-admin](#) will lock the database while copying.

The resulting backup directory is safe to handle using standard file-based backup tools like `tar` or `dump/restore`.

Please, note, that `hotcopy` command does not overwrite target directory and when such exists, `hotcopy` ends with error: `Command failed: [Errno 17] File exists: This is discussed in #3198.`

### Restoring a Backup

Backups are simply a copied snapshot of the entire [project environment](#) directory, including the SQLite database.

To restore an environment from a backup, stop the process running Trac (i.e. the Web server or [tracd](#)), restore the contents of your backup (`path/to/backupdir`) to your [project environment](#) directory and restart the service.

---

See also: [TracAdmin](#), [TracEnvironment](#), [TracGuide](#), [TracMigrate](#)