

IPSLCM6.2 configuration

Table of Content

IPSLCM6.2 configuration	1
1. Resolutions and configurations	2
1.1. How to use it	2
1.2. Restart files	3
1.3. Output level	3
1.4. Lengths, frequencies	3
1.4.1. Period length	4
1.4.2. Pack Frequency	4
1.4.3. Rebuild frequency	4
1.5. How to add a parameter in NEMO's namelist?	4
1.6. What is the maximum length for a simulation name?	4
1.7. Computing centres	4
1.7.1. TGCC Bull Curie thin nodes	4

The IPSLCM6.2 configuration is a part of the IPSLCM6 family model describes [here](#)

1. Resolutions and configurations

IPSLCM6.2 model will be available at different resolutions/configurations :

- VLR** : LMDZ 96x95x39-ORCHIDEE - NEMO-LIM2-PISCES ORCA2xL31. **under development**
- LR** : LMDZ 144x144x79-ORCHIDEE - NEMO-LIM3-PISCES eORCA1xL75
- MR1** : LMDZ 256x256x79-ORCHIDEE - NEMO-LIM3-PISCES eORCA1xL75 **under development**
- MR025** : LMDZ 256x256x79-ORCHIDEE - NEMO-LIM3 eORCA025xL75
- ESMCO2** : LMDZ 144x144x79-ORCHIDEE - NEMO-LIM3-PISCES eORCA1xL75 with interactive carbon cycle ocean/atmosphere.
- ESMAER** : LMDZ 144x144x79-ORCHIDEE-INCA - NEMO-LIM3-PISCES eORCA1xL75 with interactive aerosols on atmosphere.

IPSLCM6.2 is composed of following components and tools (Oct. 2019) :

#-H- IPSLCM6.2_work	IPSLCM6.2_work	coupled configuration				
#-H- IPSLCM6.2_work	This configuration is under construction					
#-H- IPSLCM6.2_work	NEMOGCM branch nemo_v3_6_STABLE	revision 9455				
#-H- IPSLCM6.2_work	SHACONEMO	revision 279				
#-H- IPSLCM6.2_work	XIOS trunk	revision 1659				
#-H- IPSLCM6.2_work	IOIPSL src	trunk 4432				
#-H- IPSLCM6.2_work	LMDZ6 trunk	rev 3489				
#-H- IPSLCM6.2_work	ORCHIDEE version branches/	ORCHIDEE_2_2/	ORCHIDEE revision 6189			
#-H- IPSLCM6.2_work	OASIS3-MCT 2.0_branch	rev 1818				
#-H- IPSLCM6.2_work	IPSLCM6.2 latest	revision				
#-H- IPSLCM6.2_work	libIGCM trunk	rev 1482				
#-M- IPSLCM6.2_work	arnaud.caubel@lsce.ipsl.fr					
#-C- IPSLCM6.2_work	IOIPSL/trunk	4432	8	IOIPSL	modeles	
#-C- IPSLCM6.2_work	branches/	ORCHIDEE_2_2/	ORCHIDEE	14	ORCHIDEE	modeles
#-C- IPSLCM6.2_work	branches/OASIS3-MCT_2.0_branch/oasis3-mct	1818	15	oasis3-mct	.	
#-C- IPSLCM6.2_work	LMDZ6/trunk	3559	11	LMDZ	modeles	
#-C- IPSLCM6.2_work	CONFIG/UNIFORM/v6/IPSLCM6.2	HEAD	8	IPSLCM6	config	
#-C- IPSLCM6.2_work	trunk/libIGCM	1488	10	libIGCM	.	
#-C- IPSLCM6.2_work	branches/2015/nemo_v3_6_STABLE/NEMOGCM	9455	7	.	modeles	
#-C- IPSLCM6.2_work	trunk/ORCA1_LIM3_PISCES	287	17	.	modeles/NEMOGCM/CONF	
#-C- IPSLCM6.2_work	trunk/ORCA025_LIM3_PISCES	287	17	.	modeles/NEMOGCM/CONF	
#-C- IPSLCM6.2_work	trunk/INCA6	873	9	INCA	modeles	
#-C- IPSLCM6.2_work	XIOS/trunk	1659	12	XIOS	modeles	

The default configuration LR is exactly the same describes in [IPSLCM6](#) configuration. You can choose between two experiments EXPERIMENTS/IPSLCM/pdControl_TEST and EXPERIMENTS/IPSLCM/piControl_TEST

. Here is described how to use the existing **ESM** configurations : **ESMCO2** and **ESMAER**

1.1. How to use it

To retrieve the configuration :

```
mkdir YOUR_DIRECTORY ; cd YOUR_DIRECTORY
svn_ano # svn co http://forge.ipsl.jussieu.fr/igcmg/svn/modipsl/trunk modipsl
cd modipsl/util
./model IPSLCM6.2_work
cd ../config/IPSLCM6.2
```

The compilation slightly differs from what has been done so far. Now we used a script named **compile_ipslcm6.sh** with several option (resolution, level of optimisation, full or partial recompilation) to compile the model

```
#####
# Usage of the script compile_ipslcm6.sh
#
#####

./compile_ipslcm6.sh [Options]

Options: [LR / VLR / MR1 / MR025] Model resolution, choose only one. Default: LR.
          [ESMCO2] Compile IPSLCM6 for CO2 interactif ocean/atmosphere.
          [ESMAER] Compile IPSLCM6 for AER interactif on atmosphere
          [-full] Full recompilation of all components. This option can be added to all other options.
          [-cleannemo] Full recompilation of NEMO component only.
          [-debug / -dev / -prod] Level of optimization. One of these can be added to all other compile options. Default: -p

Example 1: Default compilation of IPSLCM6 for resolution LR
           (Resolution atmos: 144x142x79, ocean: ORCA1)
./compile_ipslcm6.sh

Example 2: Compilation of IPSLCM6 for resolution MR025
           (atmos: 256x256x79, ocean: ORCA025, NOPISCES)
./compile_ipslcm6.sh MR025

Example 3: Compilation of IPSLCM6 for ESM CO2
./compile_ipslcm6.sh ESMCO2 -cleannemo

Example 4: Default resolution (LR) compiled in debug mode
./compile_ipslcm6.sh -debug

Example 5: Default compilation with full recompilation of all components. No clean is needed.
./compile_ipslcm6.sh -full

Example 6: Full recompilation of resolution MR05 in debug mode
./compile_ipslcm6.sh MR025 -debug -full
```

To compile and create the Job for **ESMCO2**

```
./compile_ipslcm6.sh ESMCO2

cp EXPERIMENTS/IPSL_ESM/CO2/piControl_TEST/config.card .
vi config.card # modify JobName (at least) : MYJOBNAME, restarts
.../..../util/ins_job # Check and complete job's header

cd MYJOBNAME
vi Job_MYJOBNAME # modify PeriodNb, adjust the time, headers ...
sbatch Job_MYJOBNAME # IDRIS
ccc_msub Job_MYJOBNAME # TGCC
```

1.2. Restart files

ESMCO2 configuration starts from IPSLCM6 **CM61-pre-pi-01** simulation (1849-12-31) available from RESTART/IPSLCM6/PROD/piControl-spinup for all the components, except for the Coupler. The latter is taken from /ccc/store/cont003/gencmip6/p86cadul/IGCM_OUT/IPSLCM6/PROD/piControl-spinup/

1.3. Output level

By default, only **monthly outputs** and **low output levels** are activated.

1.4. Lengths, frequencies

1.4.1. Period length

Default period length is 1Y, i.e in config.card :

```
PeriodLength=1Y
```

Note that clean_PeriodLength.job will remove last period files, i.e last simulated year files.

1.4.2. Pack Frequency

Default pack frequency is 1Y, i.e in config.card :

```
PackFrequency=1Y
```

1.4.3. Rebuild frequency

Since we run with XIOS (server mode) as output library, **the rebuild step is not needed anymore**.

1.5. How to add a parameter in NEMO's namelist?

- let find the parameter in namelist_ref. For example in modeles/NEMOGCM/CONFIG/SHARED/namelist_ref
- let find the namelist's name : for example &namicdyn
- let add a line with the new of the parameter in the file PARAM/namcouple_ESMCO2_ORCA1xLMD144142 in the &namicdyn section

1.6. What is the maximum length for a simulation name?

Due to limitation in NEMO, a simulation should have **less than 39 characters**.

1.7. Computing centres

1.7.1. TGCC Bull Curie thin nodes

Default configuration on **929 cores** allows you to run **13 simulated years per day**.