

## **Wikiprint Book**

**Title: 1. Resolutions and configurations**

**Subject: Igcmg\_doc - Doc/Config/IPSLCM6.2**

**Version: 24**

**Date: 06/29/24 09:37:31**

## Table of Content

<b>IPSLCM6.2 configuration - the ESM configuration</b>	<b>3</b>
<b>1. Resolutions and configurations</b>	<b>3</b>
1.1. IPSLCM	3
1.2. IPSLESM	3
<b>2. Technicals Details</b>	<b>3</b>
2.1. How to use it	3
2.2. Restart files	5
2.3. Output level	5
2.4. Lengths, frequencies	5
2.4.1. Period length	5
2.4.2. Pack Frequency	5
2.4.3. Rebuild frequency	5
2.5. How to add a parameter in NEMO's namelist?	5
2.6. What is the maximum length for a simulation name?	5
2.7. Computing centres	5
2.7.1. TGCC Bull Curie thin nodes	5

## IPSLCM6.2 configuration - the ESM configuration

The IPSL6.2 configuration is a part of the IPSL6 family model describes [here](#)

### 1. Resolutions and configurations

IPSL6.2 model will be available at different resolutions/configurations :

- **VLR** : LMDZ 96x95x39-ORCHIDEE - NEMO-LIM2-PISCES ORCA2xL31. **under development**
- **LR** : LMDZ 144x144x79-ORCHIDEE - NEMO-LIM3-PISCES eORCA1xL75
- **MR1** : LMDZ 256x256x79-ORCHIDEE - NEMO-LIM3-PISCES eORCA1xL75 **under development**
- **MR025** : LMDZ 256x256x79-ORCHIDEE - NEMO-LIM3 eORCA025xL75
- **ESMCO2** : LMDZ 144x144x79-ORCHIDEE - NEMO-LIM3-PISCES eORCA1xL75 with interactive carbon cycle ocean/atmosphere.
- **ESMAER** : LMDZ 144x144x79-ORCHIDEE-INCA - NEMO-LIM3-PISCES eORCA1xL75 with interactive aerosols on atmosphere.

**IPSL6.2** is composed of following components and tools (Oct. 2019) :

```
#-H- IPSL6.2_work IPSL6.2_work coupled configuration
#-H- IPSL6.2_work This configuration is under construction
#-H- IPSL6.2_work NEMOGCM branch nemo_v3_6_STABLE revision 9455
#-H- IPSL6.2_work SHACONEMO revision 279
#-H- IPSL6.2_work XIOS trunk revision 1659
#-H- IPSL6.2_work IOIPSL src trunk 4432
#-H- IPSL6.2_work LMDZ6 trunk rev 3489
#-H- IPSL6.2_work ORCHIDEE version branches/ORCHIDEE_2_2/ORCHIDEE revision 6189
#-H- IPSL6.2_work OASIS3-MCT 2.0_branch rev 1818
#-H- IPSL6.2_work IPSL6.2 latest revision
#-H- IPSL6.2_work libIGCM trunk rev 1482
#-M- IPSL6.2_work arnaud.caubel@lsce.ipsl.fr
#-C- IPSL6.2_work IOIPSL/trunk 4432 8 IOIPSL modeles
#-C- IPSL6.2_work branches/ORCHIDEE_2_2/ORCHIDEE 6189 14 ORCHIDEE modeles
#-C- IPSL6.2_work branches/OASIS3-MCT_2.0_branch/oasis3-mct 1818 15 oasis3-mct .
#-C- IPSL6.2_work LMDZ6/trunk 3559 11 LMDZ modeles
#-C- IPSL6.2_work CONFIG/UNIFORM/v6/IPSL6.2 HEAD 8 IPSL6.2 config
#-C- IPSL6.2_work trunk/libIGCM 1488 10 libIGCM .
#-C- IPSL6.2_work branches/2015/nemo_v3_6_STABLE/NEMOGCM 9455 7 . modeles
#-C- IPSL6.2_work trunk/ORCA1_LIM3_PISCES 287 17 . modeles/NEMOGCM/CONF
#-C- IPSL6.2_work trunk/ORCA025_LIM3_PISCES 287 17 . modeles/NEMOGCM/CONF
#-C- IPSL6.2_work trunk/INCA6 873 9 INCA mode
#-C- IPSL6.2_work XIOS/trunk 1659 12 XIOS modeles
```

#### 1.1. IPSLCM

The default configuration LR is exactly the same describes in [IPSL6](#) configuration.

- To compile you will use the target **IPSL6-LR**
- For the experiments, you can choose between `EXPERIMENTS/IPSL6/pdControl_TEST` and `EXPERIMENTS/IPSL6/piControl_TEST`

#### 1.2. IPSLESM

This configuration allow coupling with CO2 cycle or interactive aerosols calculated by Inca model. On this page we will describe how to use these 2 existing **ESM** configurations : **ESMCO2** and **ESMAER**

## 2. Technicals Details

### 2.1. How to use it

To retrieve the configuration :

```
mkdir YOUR_DIRECTORY ; cd YOUR_DIRECTORY
svn_ano # svn co http://forge.ipsl.jussieu.fr/igcmg/svn/modipsl/trunk modipsl
cd modipsl/util
./model IPSLCM6.2_work
cd ../config/IPSLCM6.2
```

The compilation slightly differs from what has been done so far. Now we used a script named **compile\_ipslcm6.sh** with several option ( resolution, level of optimisation, full or partial recompilation ) to compile the model

```
#####
# Usage of the script compile_ipslcm6.sh
#
#####

./compile_ipslcm6.sh [Options]

Options: [LR / VLR / MR1 / MR025] Model resolution, choose only one. Default: LR.
         [ESMCO2] Compile IPSLCM6 for CO2 interactif ocean/atmosphere.
         [ESMAER] Compile IPSLCM6 for AER interactif on atmosphere
         [-full] Full recompilation of all components. This option can be added to all other options.
         [-cleannemo] Full recompilation of NEMO component only.
         [-debug / -dev / -prod] Level of optimization. One of these can be added to all other compile options. Default: -p

Example 1: Default compilation of IPSLCM6 for resolution LR
           (Resolution atmos: 144x142x79, ocean: ORCA1)
./compile_ipslcm6.sh

Example 2: Compilation of IPSLCM6 for resolution MR025
           (atmos: 256x256x79, ocean: ORCA025, NOPISCES)
./compile_ipslcm6.sh MR025

Example 3: Compilation of IPSLCM6 for ESM CO2
./compile_ipslcm6.sh ESMCO2 -cleannemo

Example 4: Default resoluion (LR) compiled in debug mode
./compile_ipslcm6.sh -debug

Example 5: Default compilation with full recompilation of all components. No clean is needed.
./compile_ipslcm6.sh -full

Example 6: Full recompilation of resolution MR05 in debug mode
./compile_ipslcm6.sh MR025 -debug -full
```

To compile and create the Job for **ESMCO2**

```
./compile_ipslcm6.sh ESMCO2

cp EXPERIMENTS/IPSLESM/CO2/piControl_TEST/config.card .
vi config.card # modify JobName (at least) : MYJOBNAME, restarts
../util/ins_job # Check and complete job's header

cd MYJOBNAME
vi Job_MYJOBNAME # modify PeriodNb, adjust the time, headers ...
sbatch Job_MYJOBNAME # IDRIS
```

```
ccc_msub Job_MYJOBNAME # TGCC
```

To compile and create the Job for **ESMAER**

```
./compile_ipslcm6.sh ESMAER

cp EXPERIMENTS/IPSLESM/AER/piControl_AER_TEST/config.card .
vi config.card # modify JobName (at least) : MYJOBNAME, restarts
../util/ins_job # Check and complete job's header

cd MYJOBNAME
vi Job_MYJOBNAME # modify PeriodNb, adjust the time, headers ...
ccc_msub Job_MYJOBNAME # TGCC
```

## 2.2. Restart files

ESMCO2 configuration starts from IPSLCM6 **CM61-pre-pi-01** simulation (1849-12-31) available from RESTART/IPSCLM6/PROD/piControl-spinup for all the components, except for the Coupler. The latter is taken from /ccc/store/cont003/gencmip6/p86cadul/IGCM\_OUT/IPSCLM6/PROD/piControl-spinup/

## 2.3. Output level

By default, only **monthly outputs** and **low output levels** are activated.

## 2.4. Lengths, frequencies

### 2.4.1. Period length

Default period length is 1Y, i.e in config.card :

```
PeriodLength=1Y
```

Note that clean\_PeriodLength.job will remove last period files, i.e last simulated year files.

### 2.4.2. Pack Frequency

Default pack frequency is 1Y, i.e in config.card :

```
PackFrequency=1Y
```

### 2.4.3. Rebuild frequency

Since we run with XIOS (server mode) as output library, **the rebuild step is not needed anymore.**

## 2.5. How to add a parameter in NEMO's namelist?

- let find the parameter in namelist\_ref. For example in modeles/NEMOGCM/CONFIG/SHARED/namelist\_ref
- let find the namelist's name : for example &namicedyn
- let add a line with the new of the parameter in the file PARAM/namcouple\_ESMCO2\_ORCA1xLMD144142 in the &namicedyn section

## 2.6. What is the maximum length for a simulation name?

Due to limitation in NEMO, a simulation should have **less than 39 characters**.

## 2.7. Computing centres

### 2.7.1. TGCC Bull Curie thin nodes

Default configuration on **929 cores** allows you to run **13 simulated years per day**.